

Benefits of properly maintaining roof-mounted equipment

Roof damage is a major source of property loss each year when buildings are subjected to high winds, wind-driven rain, hail, ice, snow and wildfire. A compromised roof can lead to significant damage to internal fixtures, furniture and equipment.

What's more, rooftop equipment or pieces of the roof itself can take flight during a windstorm, causing damage to the building, nearby vehicles or even neighboring property. Proper attention to all aspects of a roof can make the difference between minimal damage and catastrophic failure during high winds.



To help business owners tackle roof issues, the [Insurance Institute for Business & Home Safety \(IBHS\)](#) has produced a series of short papers on the installation, maintenance and repair of commercial roofs.

The focus here is on roof-mounted equipment, such as HVAC, photovoltaic systems, exhaust fans, and other mechanical units, all of which are common features on many commercial rooftops. Proper maintenance of this equipment leads to long-term savings by prolonging the life of the equipment, lowering utility bills and affording greater protection in a storm.

Energy efficiency

Proper ventilation of roof-mounted air conditioners and air makeup units means greater energy efficiency, which leads to lower electric bills, a smaller carbon footprint and a more comfortable indoor climate for the building's occupants. Clogged and soiled air filters can reduce air flow and affect the unit's heating and cooling abilities. Poor ventilation also requires the unit to run for longer intervals, causing greater wear and tear on the motors and leading to a shorter operating lifetime.

Steps business owners can take:

- Replace the air filter in accordance with the manufacturer's guidelines. This is an easy and cost-effective way to help maintain a ventilation system's efficiency.

Keeping parts in good working order

Motors, bearings and belts should be well maintained in accordance with the manufacturer's maintenance guidelines to ensure proper operation of rooftop units. This will help prolong the life of the unit and prevent breakdowns, which can have cascading effects on many aspects of business operations.

Steps business owners can take:

- Keep motor and fan bearings well lubricated.
- Ensure that rubber belts have the proper tension. Belts that slip will emit a high pitched whining sound similar to an automobile's belt slipping.
- Watch for signs that rubber belts have become brittle and cracked. Remember, belts have a limited lifespan and should be inspected and replaced when directed by the manufacturer or upon signs of deterioration.

The importance of balance

Fan blades operate most effectively when they are well balanced. When the blades are unbalanced, the unit will vibrate and this may cause screws and other parts to loosen. An unbalanced fan reduces efficiency and compromises the unit's secure attachment.

Steps business owners can take:

- The greater the imbalance, the greater the vibration. This vibration may become obvious on smaller sized units but should be part of regular inspections.
- When a roof top unit begins to vibrate and shake, contact a reliable contractor to correct problems that may cause the fans to be unbalanced.

Exterior maintenance and secure attachment

Because rooftop equipment is exposed to all weather elements, it is vital to maintain the unit's exterior and make sure it is securely attached. Corrosion and deterioration are the most common problems and can allow panels or other parts to become airborne in the event of high winds.

Steps business owners can take:

- Inspect for rusted metal panels, screws and metal flashing on curbs, and replace as soon as possible.
- Inspect around the unit's connection to the curb it sits on. Check for any visible signs of potential leaks; these can be repaired using various roof sealants and caulks that are readily available.
- If it is suspected that a water leak has occurred, the curbing itself should be inspected for rotting and replaced if needed.

Check and recheck

While a local contractor or maintenance worker can perform most of the inspections and repairs that are necessary to keep rooftop equipment in good working order, it is important to inspect the equipment after the work is done to make sure all screws, cables and cable straps are tightened and back in place.

Failure to correctly reinstall screws and cables can compromise the unit's overall structural integrity and leave it vulnerable to potential damage during a windstorm. For example, the panels can tear away and skip across the roof cover. This creates water leaks and, in some cases, causes the roof cover to fail.

Steps business owners can take:

- Remind the contractor that you will not consider the job done until all parts of the unit are back in place and properly secured and all debris is removed.
- At the conclusion of rooftop equipment repair, have maintenance staff inspect the unit to make sure that screws, cables and cable straps are tightened and reconnected.
- Check the roof for miscellaneous debris, as well as tools that may have been left behind. Anything that is not firmly attached to the roof can become windborne debris in the event of a storm.

For additional information about maintaining commercial properties, please visit:

www.DisasterSafety.org/commercial_maintenance

About the IBHS

IBHS is a non-profit applied research and communications organization dedicated to reducing property losses due to natural and man-made disasters by building stronger, more resilient communities.

© 2013 Insurance Institute for Business & Home Safety

AmTrust distributes this e-newsletter as a service for its customers. It is provided in the spirit of professionals sharing their work with each other. The information provided in this document is intended for use as a guideline and is not intended as, nor does it constitute, legal or professional advice. It is not intended to provide authoritative answers to safety and health questions. AmTrust does not warrant that adherence to, or compliance with, any recommendations, best practices, checklists or guidelines will result in a particular outcome. Before using the information here, the accuracy and appropriateness of the information to your specific situation should be verified by a person qualified to assess all the factors involved.

CONTACT INFO:

PHONE: 888.486.7466 ext. 363275
WEB: www.amtrustnorthamerica.com
EMAIL: lcinfo@amtrustgroup.com

MAILING ADDRESS:

AmTrust North America, Inc.
Loss Control
2605 Enterprise Road, Suite 290
Clearwater, FL 33759